



Cross Flow Air Curtain

FEATURES

- Metal casing with durable powder spray coating.
- Unique design and slim body.
- High efficiency and low noise.
- Convenient operation, easily adjust air pattern.
- Multiple width available: 3, 4, 5 and 6 FT.
- Heights installations up to 3m.

CE ISO9001: 2015



Metal housing



Adjustable air deflector



High efficient motor



Quiet wind wheel



Remote control



Magnetic door



Two speeds



Wall base

Model	Voltage/ Frequency (V/Hz)	Impeller size (mm)	Input Power (HI/LO) (W)	Air Velocity (HI/LO) (m/s)	Air Volume (HI/LO) (m³/h)	Noise (dB)	Net Weight (KG)	Unit Size (mm)
TT-AC-FM-1009X32Y-2	220V 50/60Hz	100	100/84	11.0/9.0	1480/1210	≤43	7.3	900x180x140
TT-AC-FM-1012X32Y-2	220V 50/60Hz	100	130/110	11.0/9.0	2130/1743	≤44	9.2	1200x180x140
TT-AC-FM-1015X32Y-2	220V 50/60Hz	100	175/150	11.0/9.0	2530/2070	≤46	11.8	1500x180x140
TT-AC-FM-1018X32Y-2	220V 50/60Hz	100	213/190	11.0/9.0	2810/2299	≤48	14.0	1800x180x140
TT-AC-FM-1009X32Y-1	110V 60Hz	100	100/72	11.0/9.0	1480/1210	≤43	7.3	900x180x140
TT-AC-FM-1012X32Y-1	110V 60Hz	100	130/110	11.0/9.0	2130/1743	≤44	9.2	1200x180x140
TT-AC-FM-1015X32Y-1	110V 60Hz	100	175/150	11.0/9.0	2530/2070	≤46	11.8	1500x180x140
TT-AC-FM-1018X32Y-1	110V 60Hz	100	213/189	11.0/9.0	2810/2299	≤48	14.0	1800x180x140

Carrier InterAmerica Corp

10801 NW 103rd St, Suite, Miami, Florida 33178 | T: 305 805 4500 · www.carriercca.com