

COLDPOINT

Excelencia en Ventilación y Acondicionamiento de Aire



EQUIPO DE AIRE ACONDICIONADO
TIPO PAQUETE - ROOFTOP

10 SEER AC Package Units

- ❖ Capacity range 3 to 5 Tons.
- ❖ Quiet horizontal discharge.
- ❖ High efficiency heat exchanger.
- ❖ Convenient access panels.
- ❖ Architecturally compatible, anti-rust steel cabinets. 1,000-hour salt spray tested. Internal safeguards protect compressor against high pressure, low pressure, coil temperature and power surge.
- ❖ Electric heat kit available as a field-installed option.
- ❖ Optional wired controller and centralized controller as optional



Specifications

Nominal ton*			5
Model			CRC-60CWN1-X10(A)
Power supply			208 - 230V 3Ph~ 60Hz
Cooling	Capacity	Btu/h	60,000
		kW	17.6
	Input	kW	6.0
	EER	Btu/h.W	10.0
Air flow	Indoor side	CFM	1655
External static pressure		Pa	50
Max. power input		kW	7.8
Max. current		A	25.5
Compressor	Type / Quantity		Scroll / 1
Indoor fan	Type / Drive type		Centrifugal / Direct
Outdoor fan	Type / Drive type		Axial / Direct
Wired controller			Optional
Centralized controller			Optional
Refrigerant	Type	/	R410A
	Control	/	Capillary
	Charged	kg	2.6
		lbs	5.6
Sound pressure level		dB(A)	67.1
Ambient temperature			21°C - 46°C
Dimension	Net (W×H×D)	mm	1,116×830×744
	Packing (W×H×D)	mm	1,152×855×765
Weight	Net / Gross	kg	150/153

- Notes:
1. Cooling capacity test condition: Outdoor ambient temperature: 35°C, indoor temperature 26.7°C DB / 19.4°C WB;
 2. Sound values are measured in a semi-anechoic room, at a position 1m in front of the unit and (1 meter + height of unit)/2 above the floor.
 3. Specifications are subject to change without prior notice for product improvement.
 4. * Nominal ton only for reference.
 5. Cooling or heating capacity as per specifications.